

## Spec. of WG60C Gloss Meter

<b>Product Name</b>	Gloss meter
<b>Model</b>	WG60C
<b>Measurement Range</b>	0-200Gu
<b>Application</b>	Apply on paint, ink, stoving varnish, coating, wood products; Marble, granite, vitrified polished tile, pottery brick and porcelain, plastic, printing, paper; other metallic material.
<b>Instrument Dimensions</b>	159x49x72mm
<b>Projection Angle</b>	60°
<b>Measuring Spot</b>	(ellipse: long axis*minor axis) 14mm*61mm
<b>Measuring Mode</b>	Automatic measurement/ manual measurement/sin measurement/average measurement and cross measurement for a variety of combination measuring mode
<b>Standard Setting</b>	<b>Sample</b> Manually setting standard and tolerance to determine “pass” or “failure”.
<b>Data Storage</b>	100 groups set standard sample in any stored data, user-define the tolerance range
<b>Language</b>	Chinese/English
<b>Output</b>	connect the micro printer to realize real-time output of measured data
<b>Division Value</b>	0.1Gu
<b>Repeatability</b>	0.2Gu
<b>Reproducibility</b>	0.4Gu
<b>Indication Error</b>	1.0Gu
<b>International Standard</b>	ISO—2813、ASTM—C584、ASTM—D523、DIN—67530、ASTM—D2457、60° JND-A60、JND-P60
<b>National Standard</b>	60° GB 9754、GB 9966、GB 8807
<b>Standard Accessories</b>	Power adapter/user manual/warranty certification/standard board
<b>Optional Accessories</b>	micro-printer



**WG60C Out looking**